

Power management for energy harvesting based systems

Alain Pegatoquet
(Andrea Castagnetti PhD thesis)


Agenda

1. Introduction and motivations
2. Related works
3. System modeling
4. Power management for energy harvesting WSN nodes
 - a) Open-loop energy neutral power manager
 - b) Closed-loop: OL plus negative energy power manager
5. A joint Duty-Cycle and Transmission Power Management Approach for EH-WSN
6. Simulation results
7. Conclusion

1. Introduction and Motivations

What kinds of issues are addresses?


- Communicating objects able to **collect and process data** (wireless sensor networks)
- **Deployment** of these objects has just started...



Source: SensLab


- Power-autonomous objects
 - Harvesting
 - Storage
- An optimized power consumption management (power manager)

- Mobility



Source: Mercedes

Designing Autonomous Communicating Objects




- **Energy Harvesting:** a **new paradigm** for power management
 - The objective is to **balance** (in average) the consumed energy and the harvested energy in order to optimize performance
 - ➔ **E**nergy **N**eutral **O**peration (**ENO**)

$$\text{Harvested Energy} = \text{Consumed Energy}$$

- The system lifetime can (in theory) lasts forever...


Designing Autonomous Communicating Objects



■ 3 different modes :

- Energy-**neutral** $E_H = E_C$
- **Negative**-Energy $E_H < E_C$
- **Positive**-Energy $E_H > E_C$


Designing Autonomous Communicating Objects



- Harvested Energy (environment) : availability is hard **to control**
- Consumed Energy : **controllable**
 - PHY, MAC, NWK layers
 - RF chip (TX power)
 - Low Power Modes ➔ **Power Manager**

Power Manager

- How to **control the power consumption** of the communicating object?
 - Adapt the wake-up period of the node (T_{wi})
 - Transmit Power (P_{TX})
- **Consumed Energy**
 - Off line characterization of **nodes activities** (Look-Up Table)
 - Depends on **scenario** or **functional modes**
- **Harvested Energy** models
 - Either **predictions** or **measures** (ex. light sensor)



Power Manager


- Which kind of **energy storage** element?
 - Battery or super capacitor?

[Cymbet 2011]




- **500** recharge cycles
- Difficult to know the state of charge with accuracy
- + **Low leakage current and big capacity**

[HZ202F 2013]



- + **500 000**
- + Easy to know the state of charge
- High leakage current

Power Manager



- Constraints for power management
 - ➔ Low complexity
 - ➔ $T_{PM} = n * T_{WI}$


2. Related Works

Kansal et al.

- Kansal et al. were the first to propose **a simple solar energy prediction algorithm** to support their harvested-energy management approach.
- The predictor is based on an **Exponentially Weighted Moving Average (EWMA)** of historical data:

$$\bar{x}(i) = \alpha \bar{x}(i-1) + (1 - \alpha)x(i)$$


- The day is divided into **slots**.
- Each slot is **30 minutes long**, as the variation in generated power level is assumed to be small within a 30 minute duration.



[Kansal 2007]

Recas et al.

- Recas et al. propose a prediction algorithm named **Weather-Conditioned Moving Average (WCMA)** to take into account both the current and past-days weather conditions.
- Drawback of EWMA (Kansal):




When the sunny and cloudy days alternate, the EWMA produces a significant error in its prediction, **due to the high impact of the solar conditions of previous day** in the predicted value.

- To avoid this effect, Recas et al. propose a prediction algorithm that takes into account not only the solar conditions at a specific time of the day, **but also the weather conditions in the current day.**


[Recas 2009]

$$E(d, n+1) = \alpha \cdot E(d, n) + GAP_k \cdot (1 - \alpha) \cdot M_D(d, n+1)$$

- WCMA algorithm uses an **E matrix of size D x N** that stores N energy values for each D past days.



- Comparison of WCMA vs. EWMA



Day	E_{realJ}	Algorithm	EJ	Err%
7	571.72	WCMA	550.44	3.72
		EWMA	535.50	6.34
8	284.63	WCMA	255.60	10.20
		EWMA	543.60	-90.99
9	400.61	WCMA	360.00	10.14
		EWMA	423.00	-5.59
10	609.50	WCMA	597.60	1.95
		EWMA	406.80	33.26

- Over all 45 days of the collected solar panel data, **EWMA gives an average error of 28.6% compared to 9.8% obtained with WCMA** algorithm.

[Recas 2009]


Conclusion

- **Kansal approach** (EWMA-based algorithm) is accurate for consistent weather conditions, but **when cloudy and sunny days alternate**, recent days energy values introduce **significant prediction errors**.
- In other hand, **WCMA based approach** (Recas et al.) takes into account weather changes but introduces a **non significant CPU overhead and memory footprint**.
- Moreover, none of these approaches takes into account the **State of Charge (SoC)** of the battery for optimizing the power manager decisions and avoiding a complete discharge of the battery...
- Finally, a wake-up period of 30 minutes for the power manager seems to be too slow for a good system reactivity.


3. System Modeling

Global View of the System


- Generic Solar Harvesting Systems



- Battery Centric Modeling



A Periodic Task-level Platform Load Model



- Q_{sense} : charge consumed for a sensing operation [Coulomb].
- Q_{tx} : charge consumed for a RF transmission [Coulomb].
- Q_{rx} : charge consumed for a RF transmission [Coulomb].
- T_{wi} : wake-up period for sensing [seconds].
- T_{tx} : RF transmission period (multiple of T_{wi}) [seconds].
- T_{fwd} : Forwarding transmission period (multiple of T_{wi}) [seconds].

- Rate of discharge of the battery (α)

$$\alpha = \frac{Q_i}{T_i} [\text{C/s}] \text{ or } [\text{A}]$$


[Castagnetti 04-2012]

A Battery and Energy Harvesting Integrated Model

- Rate of recharge of the battery (β)
 - β is expressed in Ampere and **indicates the rate at which the energy harvester can recharge the battery** under a fixed amount of energy available from the environment.
 - The β parameter models both the **efficiency of the energy harvester** and the **efficiency of the voltage regulator** and **the charge circuit** that are used to recharge the battery.

A Battery and Energy Harvesting Integrated Model


- Rate of recharge (β) for different light conditions



A Battery State of Charge Model for Periodic Workload

State of Charge (SoC) Estimation

- The SoC depends upon:
 - The **harvested** energy (β).
 - The **platform load** current consumption ($\alpha = \frac{Q_i}{T_{Wi}}$)
 - The **leakage** current (battery self discharge and low-power mode current consumption).



The State of Charge (SoC) of a battery for n wake-up periods (T_{wi})

$$SoC(t + nT_{Wi}) = SoC(t) + [\beta - (\alpha_s + \alpha_{Tx} \frac{T_{Wi}}{T_{Tx}} + \alpha_{fwd} \frac{T_{Wi}}{T_{fwd}})] \times nT_{Wi} - K_{leak} \times nT_{Wi}$$

Conditions

$$SoC(t = 0) = SoC_{max}.$$

$$SoC_{min} \leq SoC(t + n T_{wi}) \leq SoC_{max}.$$


$$\beta, \alpha_s \text{ and } \alpha_{Tx} \text{ are constants on } [t, t + n T_{wi}].$$

[Castagnetti 04-2012]


Model Validation

Case Study: Model Validation Using the EZ430 platform

- Texas Instruments EZ430 solar energy harvesting platform
 - MSP430 microcontroller (cadenced at 16MHz) and a CC2500 RF transceiver.
 - 2.25in x 2.25in solar panel.
 - Two lithium thin-film 50 μ Ah rechargeable batteries.



Access Point



End Devices

Model Validation

Case Study: Model Validation Using the TI EZ430 platform

- Platform load characterization (Q_i)




$$\begin{aligned}
 Q &= [(2,8\text{mA} \cdot 3,4\text{ms}) + (13,8\text{mA} \cdot 1\text{ms}) + \\
 &\quad (23,4\text{mA} \cdot 1,4\text{ms}) + (2,8\text{mA} \cdot 7\text{ms}) + \\
 &\quad (5\text{mA} \cdot 10,6\text{ms})] \\
 &= 9,52\mu\text{As} + 13,8\mu\text{As} + 32,76\mu\text{As} + 19,6\mu\text{As} + 53\mu\text{As} \\
 &= 128,68\mu\text{As} \\
 &= \mathbf{0,0357\mu\text{Ah}}
 \end{aligned}$$

SoC_{min}	SoC_{max}	C_d
$[\mu\text{Ah}]$	$[\mu\text{Ah}]$	$[\mu\text{Ah}]$
37	100	63

- The platform load characterization is performed by measuring the current consumed for the different tasks (TX, RX, CPU...) of an end-device.

Model Validation

Case Study: SOC Model Validation Using the EZ430 platform



- Experimental results: **lifespan prediction** (in minutes)

T_{wi} [sec]	α [μ A]	0 lux		$\simeq 200$ lux	
		LT	LT	LT	LT
		(exp)	(model)	(exp)	(model)
1	128.52	28	29	50	38
2	64.26	54	59	140	112
3	42.84	83	88	312	332
4	32.13	107	117	/	$+\infty$
6	21.42	162	176	/	$+\infty$
10	12.85	290	294	/	$+\infty$
20	6.43	585	587	/	$+\infty$

16,8% error margin when $\beta = \sim 200\text{lux}$

$\beta \geq \alpha$

5,5% error margin when $\beta = 0$

4. Power Management for Energy Harvesting WSN Nodes


Balancing the Harvested and Consumed Energy

- Adapting the performance and the power consumption of the system to the available energy (i.e. β).
- Performance scaling is achieved by varying the wake-up period (T_{wi}) of the sensor node (i.e. α).
- The objective is to operate in **Energy Neutrality** (ENO)
 - ➔ balancing the α and β parameters.
- Hypothesis:
 - The power manager must measure/estimate β .
 - The values of α are known (Q_i off-line profiling).
- Consequence:
 - In energy neutrality, SoC(t) is constant over time: $SoC(t) = SoC(t + n T_{wi})$

Balancing the Harvested and Consumed Energy

An Open-Loop Energy Neutral Power Manager (OL-PM)

Architecture



Equations

- Power Management software timer

$$T_{pm} = n T_{wi}$$

- Energy Neutral wake-up period

$$SoC(t) = SoC(t + n T_{wi}) - Q_{pm}$$




$$T_{wi} = \left\lceil \frac{Q + Q_{pm}/n}{\beta - K_{leak}} \right\rceil$$

Ceil function returns the smallest following integer

5. Simulation Results

Simulation setup

- The values of Q_{sense} and Q_{Tx} have been measured with the TI EZ430 platform.
- β is estimated from light intensity measurements taken in an office (indoor conditions) at 5-second intervals during 5 days using a lux-meter.



Harvested energy
over 5 days

Evaluation Metrics

- **Average data-Rate** (**<Rd>**): the average throughput is computed over the five days, including the periods of time where the battery is fully discharged.

$$\langle Rd \rangle = \frac{Packet_{payload}}{\overline{T}_{wi}}$$

$$Packet_{payload} = 33 \text{ bytes}$$

- **Maximum and minimum data-rate** (**Rd_{max}**, **Rd_{min}**): peak and minimal achievable performance of a node using a given power manager.
- **Average SoC** (**<SoC>**): to assess if the power management algorithm drifts in energy-neutral condition.
- **Battery failures** (**B_f**): a value of 0 means that the battery is never fully discharged and the node is always operational. Otherwise, it exists at least a $t^* \mid SoC(t^*) < SoC_{min}$

Performance Analysis and Comparison


- The OL-PM has been simulated over the five-day data-set.
- A state of the art power manager ([Kansal 2007]) for solar energy harvesting WSN has been implemented and simulated over the same data-set.
- Power Managers comparison:

	$\langle Rd \rangle$	Rd_{max}	Rd_{min}	$\langle SoC \rangle$	B_f
	[bits/s]	[bits/s]	[bits/s]	[μ Ah]	
Kansal	29.55	132	0	65.81	9
OL-PM	44.61	132	2.2	88.8	0


- The average **data-rate is improved by 51%** using the OL-PM.
- The OL-PM always provide **a minimum QoS** ($Rd_{min} \neq 0$).
- Remark: Simulating the five-day data-set **takes about 2 minutes** using a laptop PC equipped with an Intel Core-i5 CPU cadenced at 2.5 GHz and 3.8 GB of RAM.

Execution Traces

OL-PM



Kansal




- The Open-Loop power manager avoids battery failures but does partially exploits the battery capacity...

A Closed-Loop Energy Power Manager (CL-PM)

Architecture

- The CL-PM is composed of same building blocks as the OL-PM, plus the **negative-energy** power manager, the **Zero-Energy-Interval (ZEI) predictor** and the **SoC predictor**.




- Two power management strategies are available: the **energy-neutral** and the **negative-energy**.
- Closed-loop** is used as the output signal ($SoC(t)$) is fed back into the input of the negative-energy power manager block.

[Castagnetti 05-2012]

The Zero-Energy Interval (ZEI) Predictor


- Block Diagram



- ZEI**: a **Boolean that indicates if the incoming $\beta \leq \beta_{th}$** . An hysteresis comparator is used to prevent oscillations.
- D_{ZEI}** : an integer value expressed in seconds used to **estimate the ZEI duration**. This value is computed as the average of the last four measured D_{ZEI} . If less than four measures are available, a default value of 14 hours (50400 seconds) is used.

Estimation of the Zero-Energy Intervals


- Behavior of the ZEI predictor during the 5-day data-set



The hysteresis of the comparator prevents undesired oscillation of the ZEI signal and thus provides an accurate estimation of the ZEI duration.

A Closed-Loop Energy Power Manager (CL-PM)

- Problem: finding the next wake-up period T_{wi} that prevents a complete discharge of the battery.



Equations

- If we call t^* the start of a ZEI, the condition that must be respected is:

$$SoC(t^*) - (\alpha + K_{leak})D_{ZEI} \geq SoC_{min} + M$$



$$T_{wi} \geq \frac{Q D_{ZEI}}{SoC(t^*) - K_{leak} D_{ZEI} - (SoC_{min} + M)}$$

where

- $SoC(t^*)$ is the state of charge of the battery at the beginning of the ZEI,
- D_{ZEI} is an estimation of the duration of the ZEI,
- M is the battery discharge margin

Performance Analysis and Comparison


- The CL-PM has been simulated over the five-day data-set.
- Power Managers comparison:

	$\langle Rd \rangle$	Rd_{max}	Rd_{min}	$\langle SoC \rangle$	B_f
	[bits/s]	[bits/s]	[bits/s]	[μ Ah]	
Kansal [8]	29.55	132	0	65.81	9
OL-PM	44.61	132	2.2	88.8	0
CL-PM	45.87	132	0.37	69.27	0


- The Closed-Loop Power Manager:
 - slightly (globally) improves the average data-rate
 - Does not lead to battery failures
 - Decreases the $\langle SoC \rangle$...

Execution Traces

OL-PM
(n=10)




CL-PM
(n=10, M=3.15 μAh)



- The Closed-Loop power manager better exploits the battery capacity
- It provides better QoS during the night...

6. A joint Duty-Cycle and Transmission Power Management Approach for EH-WSN

Overview and Results



- According to the **received signal strength** (RSSI), the PM will adapt the transmit power of the node, thus its power consumption...
- CL-PM determine the next wake-up period (T_{wi}) according to the new transmission power ($Q_{TX}(tp_j)$)
- This approach provides up to **26% energy saving**



PowWow
UMR IRISA
UNIVERSITÉ DE
RENNES 1

	Speed [m/s]	PRR (%)	E_u [μ J]	Energy Gain (%)
CLPM-Fixed	0.2	97	210	
	0.4	95	196	
CLPM-PTPC	0.2	93	155	26.2
	0.4	89	160	23.6

7. Conclusions

Conclusions

Modeling

- A high-level modeling approach for energy harvesting WSN nodes.
- Using α and β models, the system can be described in a compact form.

Power Management

- Up to 50% data-rate improvement compared to a state of the art power manager.
- System robustness is improved by avoiding the battery to discharge too deeply.
- A global approach is needed for an efficient wake-up period adaptation (channel conditions, TX power, etc.)

References

- [Kansal 2007] A. Kansal et al., *Power management in energy harvesting sensor networks*, ACM Transactions on Embedded Computing Systems (TECS), vol.6, 2007
- [Recas 2009] Recas Piorno et al., *Prediction and management in energy harvested wireless sensor nodes*, Proceedings of the 1st International Conference on Wireless Communications, Vehicular Technology, Information Theory and Aerospace & Electronic Systems Technology (VITAE), vol. 1, num. 1, p. 6-10, Aalborg, Denmark, 17-20 May, 2009.
- [Ali 2010] Ali Mustafa et al., *Evaluation and design exploration of solar harvested-energy prediction algorithm*, Design Automation and Test in Europe (DATE), Dresden, Germany, pp. 142-147, 8-12 March 2010.
- [Moser 2010] C. Moser, L. Thiele, D. Brunelli, and L. Benini. *Adaptive Power Management for Environmentally Powered Systems*, IEEE Transactions on Computers, Vol 59, issue 4, pp. 478-491, April 2010.
- [Ferry 2011] N. Ferry et al., *Power/Energy Estimator for Designing WSN Nodes with Ambient Energy Harvesting Feature*, EURASIP Journal on Embedded Systems, Volume 2011, January 2011.
- [Castagnetti 04-2012] A. Castagnetti, A. Pegatoquet, C. Belleudy and M. Auguin, *An Efficient State of Charge Prediction Model for Solar Harvesting WSN Platforms*, 19th IEEE International Conference on Systems, Signals and Image Processing (IWSSIP), Vienna, Austria, 11-13 April, 2012.
- [Castagnetti 02-2012] A. Castagnetti, A. Pegatoquet, C. Belleudy and M. Auguin, *An Open-Loop Energy Neutral Power Manager for Solar Harvesting WSN*, 2nd International Conference on Pervasive and Embedded Computing and Communication Systems (PECCS), Rome, Italy, 24-26 February, 2012.
- [Castagnetti 05-2012] Andrea Castagnetti, Alain Pegatoquet, Cécile Belleudy and Michel Auguin, *A Framework for Modeling and Simulating Energy Harvesting WSN nodes with Efficient Power Management Policies*, Submitted to EURASIP Journal on Embedded Systems.

Thank you !

Any questions?